


REVISIONS		
Rev	DESCRIPTION	DATE
A	INITIAL RELEASE	



OPTICAL TEST DATA @ 1550NM	
INSERTION LOSS	MAX .5dB
BACK REFLECTION	MIN 55dB
FERRULE COMPRESSION	7.8N TO 11.8N
OS2 9µ	CORNING CLEARCURVE SMF28 ULTRA
ATTENUATION	0.5dB/KM @ 1310NM 0.4dB/KM @ 1550NM
BANDWIDTH	-
LINK LENGTH (10GB/S)	-

YY = AVAILABLE COLOURS	
BL	BLUE
OR	ORANGE
GN	GREEN
BR	BROWN
GR	GREY
WH	WHITE
RD	RED
BK	BLACK
YL	YELLOW
VT	VIOLET
PK	PINK
AQ	AQUA

NOTE:	
1	DUPLEX ZIP PATCH CORD
2	LOW-SMOKE, ZERO-HALOGEN PER IEC 60332-1
3	STANDARD BLACK BOX LENGTH TOLERANCE
4	CHANNEL MARKERS AND COLOR CODED BOOTS
5	TEST RESULTS SUPPLIED WITH EACH ASSEMBLY
6	PACKAGED INDIVIDUALLY
7	12 COLORS AVAILABLE
8	ROHS COMPLIANT
9	XXX = LENGTH IN METERS
10	YY = COLOR OF JACKET

BLACK BOX LENGTH TOLERANCE		
0 TO 3 METERS	-0	+7.6 CM
3 TO 30.5 METERS	-0	+15.2 CM
30.5 METERS OR MORE	-0	+30.48 CM

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±
ANGULAR: MACH ± BEND ±
TWO PLACE DECIMAL ±
THREE PLACE DECIMAL ±
INTERPRET GEOMETRIC
TOLERANCING PER:
MATERIAL:
FINISH:
DO NOT SCALE DRAWING

The information contained in this document is the sole property of Black Box Corporation of Pennsylvania. Any reproduction in part or whole without the written permission of Black Box Corp. is prohibited.
© Copyright 2012 Black Box Corporation of Pennsylvania d/b/a Black Box Network Services. All Rights Reserved.



NAME	DATE	TITLE:	REV
DRAWN: JDJHW	12/01/2016	LC - LC FIBER OPTIC PATCH CORD	A
ENG APPR: STEVEN	12/01/2016	SIZE DWG. NO. B FOLZHSM-XXX-LCLC-YY	
CHECKED: STEVEN	12/01/2016	SCALE: 1:1	
COMMENTS:			