

DATA SHEET

KTS24H

LCD CONSOLE TRAY, 24", WUXGA

24/7 TECHNICAL SUPPORT AT 877.877.2269 OR VISIT BLACKBOX.COM



BLACK BOX®

OVERVIEW

LCD CONSOLE TRAY, 24", WUXGA DATA SHEET

FEATURES

- 1U 24" LED-backlit LCD console drawer
- Left-side open
- 1920 x 1200 WUXGA native resolution/16.7M colors
- HDMI 1.4 + VGA video input/USB KB/MS
- 104-key USB keyboard with either touchpad or trackball
- One-man installation design
- Enhanced aesthetics with new molded front panel and 2-point lock
- 2-year standard warranty (upgradable up to 5 years)

OPTIONS

- Dual stereo speakers for HDMI (HS4.4)
- DVI-D (DVI)
 - *No HDMI after integration of DVI option
- 3G/HD/SD-SDI Broadcast-grade input + Speakers (SDI)
 - *No HDMI after integration of SDI option
- Front USB hub port for device access (USB)
- DC power: 12V/24V/48V/125V/250V
- SUN Micro keyboard option
- Touchscreen: Resistive 1-pt.

SPECIFICATIONS

LCD CONSOLE TRAY, 24", WUXGA DATA SHEET

LCD CONSOLE TRAY, 24", WUXGA (KTS24H) SPECIFICATION TABLE

SPECIFICATION	DESCRIPTION
CONSOLE PORT	
VIDEO INPUT	HDMI 1.4 + VGA
KB/MS	USB interface
VGA CONSOLE 6FT CABLE (OPTIONAL): KLCBLVGA62 OR HDMI CONSOLE 6FT CABLE (INCLUDED)	Drawer end: DB-15 + USB type A x 2; Server end: DB-15 + USB type A x 2 Drawer end: HDMI + USB type A x 2; Server end: HDMI + USB type A x 2
VIDEO OPTION	
DIGITAL	DVI-D DVI-D single link
PHYSICAL	
PRODUCT DIMENSIONS' (H X W X D)	Single Console: 1.73"H x 17.4"W x 27.2"D (44 x 442 x 690 mm); Console with KVM: 1.73"H x 17.4"W x 31.5"D (44 x 442 x 800 mm)
PACKING DIMENSIONS' (H X W X D)	Single Console/Console with KVM: 5.4"H x 23.2"W x 38"D (136 x 590 x 965 mm)
NET WEIGHT	Single Console: 33.7 lb. (15.3 kg); Console with KVM: 35.4 lb. (16.1 kg)
GROSS WEIGHT	Single Console: 42.9 lb. (19.5 kg); Console with KVM: 48.4 lb. (22 kg)
MOUNTING DISTANCE	Single Console Drawer: 26" ~ 35" (660 ~ 890 mm); Console with KVM drawer: 26" ~ 38.2" (660 ~ 970 mm)

'All dimensions stated are subject to change if options are selected/integrated to base model part codes.



SPECIFICATIONS (CONTINUED)

LCD CONSOLE TRAY, 24", WUXGA DATA SHEET

LCD CONSOLE TRAY, 24", WUXGA (KTS24H) SPECIFICATION TABLE (CONTINUED)

SPECIFICATION	DESCRIPTION
LED-BACKLIT LCD PANEL	
PANEL SIZE (DIAGONAL)	24.1"
NATIVE RESOLUTION	1920 x 1200
BRIGHTNESS (CD/M ²)	300
CONTRAST RATIO (TYP.)	1000:1
COLORS	16.7 M
VIEWING ANGLE (L/R/U/D)	89/89/89/89
RESPONSE TIME (MS)	14
DOT PITCH (MM)	0.27
DISPLAY AREA (MM)	518.4H x 324V
SURFACE TREATMENT	Anti-glare, Hard-coating
SURFACE HARDNESS	3H
BACKLIGHT TYPE	LED
MTBF (HRS)	30,000
ENVIRONMENT	
TEMPERATURE	Operating: 32 to 131°F (0 to 55°C); Storage: -4 to 140°F (-20 to +60°C)
HUMIDITY	Operating: 10~90%, non-condensing; Storage: 5~90%, non-condensing
ALTITUDE	Operating: 16,000 ft.; Non-operating: 40,000 ft.
SHOCK	10G acceleration (11ms duration)
VIBRATION	10~300Hz 0.5G RMS random vibration
POWER	
INPUT	Auto-sensing 100 to 240VAC, 50/60Hz
CONSUMPTION (CONSOLE/KVM)	Screen on: Max. 33W/Max. 65W; Power saving mode: Max. 2W/Max. 30W; Power button off: Max. 1W/Nil
COMPLIANCE	
EMC	FCC & CE
SAFETY	CE/LVD & UKCA
ENVIRONMENT	REACH & RoHS3/WEEE
IP CONSOLE	
CONNECTOR	RJ-45
USER MANAGEMENT	1 active user, 15-user login
NETWORK PROTOCOL	DHCP/BOOTP/DNS
SECURITY	TLS 1.3, AES, LDAP, Active Directory (AD), HTTP(s)
BROWSER	Chrome, Firefox, Edge, etc.
RESOLUTION	16:9 - max. 1920 x 1080/16:10 - max. 1920 x 1200/4:3 - max. 1600 x 1200
KEYBOARD	Supporting Layouts: America: US; EMEA: U.K., Germany, France, Russia, Spain, Italy, Switzerland
STANDARD WITH TOUCHPAD	
STANDARD WITH TRACKBALL	



ORDERING INFORMATION

LCD CONSOLE TRAY, 24", WUXGA DATA SHEET

ITEM	CODE
LCD Console Tray, 24", WUXGA	KTS24H

KTS24H MODEL WITH KVM							
	IP	REMOTE	8-PORT	12-PORT	16-PORT	32-PORT	CABLES
2K KVM	0	0	8H2K	—	—	—	KVM Cables: KLCBLDVD2K6 (6 ft.) DVI-D KVM cable; KLCBLHDM6 (6 ft.) HDMI KVM cable Resolution Support: 16:9 - max. 2560 x 1440 16:10 - max. 1920 x 1200 4:3 - max. 1600 x 1200
DVI-D KVM	0	0	—	12D	—	—	DVI Cables: KLCBLDV06 (6 ft.); KLCBLDV15 (15 ft.) Resolution Support: 16:10 - max. 1920 x 1200 16:9 - max. 1920 x 1080 4:3 - max. 1600 x 1200
CAT6 MATRIX KVM	1	1	—	—	16CXM3P	—	Server Access Modules: KLCIMUSBC USB-C dongle; KLCIMDP DP-USB dongle; KLCIMHDMI HDMI-USB dongle; KLCIMDV DVI-USB dongle; KLCIMVGA VGA-USB dongle Resolution Support: 16:10 - max. 1920 x 1200 16:9 - max. 1920 x 1080 4:3 - max. 1600 x 1200
	2	1	—	—	—	—	
	0	1	—	—	16CX2	32CMR	
	0	2	—	—	—	—	
	0	3	—	—	—	—	
CAT6 COMBO KVM	1	0	8CXC2P	—	16CX2P	—	
	0	1	8CXC2	—	16CX2	32CMR	
	0	0	8CXC	—	16CX	32CM	
DB-15 COMBO KVM	1	0	8V2P	—	—	—	VGA Cables: KLCBLVGA6 (6 ft.); KLCBLVGA10 (10 ft.); KLCBLVGA15 (15 ft.) Resolution Support: 16:10 - max. 1920 x 1200 16:9 - max. 1920 x 1080 4:3 - max. 1600 x 1200
	0	1	8V2	—	—	—	
	0	0	8V	—	16V	—	

ABOUT BLACK BOX

Black Box® is a trusted IT solutions provider delivering cutting-edge technology solutions and world-class consulting services to businesses on every continent. The breadth of our global reach and depth of expertise accelerate customer success by bringing people, ideas, and technology together to solve real-world business problems. Our IT infrastructure solutions, services, and products enable secure, flawless connectivity and meaningful collaboration across town or around the globe. To learn more, visit the Black Box website at <https://www.blackbox.com>. Follow the company on Twitter @BlackBox_ns.

Black Box and the Double Diamond logo are registered trademarks of BB Technologies Inc. All other trademarks referenced herein are the property of their respective owners.

DISCLAIMER

Black Box Corporation shall not be liable for damages of any kind, including, but not limited to, punitive, consequential or cost of cover damages, resulting from any errors in the product information or specifications set forth in this document and Black Box Corporation may revise this document at any time without notice.

EN_KVM_Datasheet_KTS24H_Rev1_2411.PDF

© COPYRIGHT 2024. BLACK BOX CORPORATION. ALL RIGHTS RESERVED.

