




BLACK BOX[®]

NETWORK SERVICES

DATA



10/100 Network Isolator




- 10/100BaseTX Ethernet (RJ-45) without PoE in.
- 10/100BaseTX (RJ-45) without PoE out.
- Works fully transparent with 3kV galvanic isolation (mandatory for medical technologies).
- Overvoltage 1500V.
- Approval for medical applications (DIN EN 60601-1).

The 10/100 Network Isolator connects a medical device or system equipped with a network interface to a non-medical device such as a single PC or complete standard office network. The Network Isolator electrically isolates both systems with up to 3kV, while maintaining all relevant standards for the electrical security.

Waiving a network isolation could result in severe damages to you and your in-patients. In that case a failure of a device anywhere in the connected system - medical or non-medical - may cause high stray currents and heat losses or break protective conductors and destroy life-supporting technologies. Therefore especially in medical applications all connected devices must comply with the DIN EN 60601-1 Standard for electrical security. And devices compatible to this standard usually cost a dear price.

The Network Isolator now minimizes these risks to a well tolerated degree by keeping currents outside of the treatment locations. In addition its small price fits even into tight budgets.

VOICE



HOTLINE



Black Box Network Services

Find us worldwide:

Austria	Australia
Belgium	Brazil
Canada	Chile
Denmark	Finland
France	Germany
Ireland	Italy
Japan	Luxembourg
Malaysia	Mexico
Netherlands	Norway
New Zealand	Puerto Rico
Singapore	Spain
Sweden	Switzerland
UK	USA

ORDER INFORMATION

Description

10/100 Network Isolator

Item number

SPM110

Contact us worldwide: www.blackbox.eu

Datasheet: 48110

Page 1/1